

EAGLE X PRO



D5 MOUNT

The **D5 Mount (D5-M)** powered by patented Corona Discharge Bipolar Ionization technology. This technology allows for continuous production of an equal amount of positive and negative ions at the highest density available on the market. The unit operates on 24VAC. The unit can be mounted with screws or magnets at the fan inlet of an air handling unit, fan coil unit, PTAC, heat pump or even on a VRF ductless split system.

SPECIFICATIONS:

Recommended CFM	Up to 2,400
Ion output (Ions/Sec)	Up to 10 Billion per second
Emitter Points	Nickel Plated Needles
Input voltage	24VAC
Power Consumption	Average 30mA
Operation environment	Temp. (14°F) – (158°F), Hum. <70%
Storage environment	Temp. (14°F) – (158°F), Hum. <85%
Ozone	< 0.005 ppm
LED Indicator	Blue "on"
Color	Black
Weight	0.4 Lb
Certifications	UL, CSA, CE, IEC, FCC, RoHS 2 compliant
Ion Balance	Inherently self-balancing system < ± 30V

DIMENSIONS: SEE FIGURE 1

STATUS INDICATOR:

The LED indicator function provides an electronic signal only when the unit is operating properly, i.e. when the unit is emitting ions.

NEUTRALIZES:

Viruses, Bacteria, Mold Spores, Fungi and Smoke*

CERTIFICATIONS: UL 867, UL 2998



* Ion output and Ion concentration in the space may change (changes in airflow, humidity, temperature, CFM, HVAC system, structure, room size ect).

*In a lab setting

Disclaimer - EXP ionization technology is not a medical device aimed to treat symptoms and/or cure any disease, including COVID-19 and/or any other medical condition.

